

A high-quality, eco-friendly & reliable partner for your wrappers!

FiberFilm™ is a stretch film reinforced with Fibers based on a patent-protected innovative design. The Fiber reinforcements provide **excellent tear resistance**, enabling the film to be stretched optimally reaching the **ultimate holding force** for your pallet.

The performance benefits allow for plastic reduction: Replace your film with **FiberFilm™** and achieve significant material savings, **exceeding 50% plastic usage reduction**.

The **FiberFilm™** performs at high settings, without breakages, ensuring an **uninterrupted production process**.



for Semi-Automatic Wrapping Machines
with **BRAKE TENSION SYSTEM**

ALPHA-L

Light applications.
Replace any 17µm film,
and adjust the tension to
exceed 50% material saving.

ALPHA-GP

General Purpose applications.
Replace any 20µm film,
and adjust the tension to
exceed 50% material saving.

ALPHA-HD

High Demanding applications.
Replace any film >23µm,
and adjust the tension to
exceed 50% material saving.



for Power Pre-Stretch Wrapping Machines
with **PRE-STRETCH RATIO UP TO 180%**

BETA-L

Light applications.
Pre-stretch ratio up to 160%.
Replace any 17µm film,
and adjust the tension to
exceed 50% material saving.

BETA-GP

General Purpose applications.
Pre-stretch ratio up to 170%.
Replace any 20µm film,
and adjust the tension to
exceed 50% material saving.

BETA-HD

High Demanding applications.
Pre-stretch ratio up to 180%.
Replace any film >23µm,
and adjust the tension to
exceed 50% material saving.



for Power Pre-Stretch Wrapping Machines
with **PRE-STRETCH RATIO UP TO 280%**

GAMMA-SL

Super light applications.
Pre-stretch ratio
up to 240%,
recommended
up to 220%.

GAMMA-L

Light applications.
Pre-stretch ratio
up to 260%,
recommended
up to 240%.

GAMMA-GP

General Purpose applications.
Pre-stretch ratio
up to 270%,
recommended
up to 250%.

GAMMA-HD

High Demanding applications.
Pre-stretch ratio
up to 280%,
recommended
up to 260%.



for Advanced Technology Wrapping Machines
with **PRE-STRETCH RATIO UP TO 320%**

DELTA-SL

Super light applications.
Pre-stretch ratio
up to 240%,
recommended
up to 220%.

DELTA-L

Light applications.
Pre-stretch ratio
up to 280%,
recommended
up to 260%.

DELTA-GP

General Purpose applications.
Pre-stretch ratio
up to 300%,
recommended
up to 270%.

DELTA-HD

High Demanding applications.
Pre-stretch ratio
up to 320%,
recommended
up to 300%.

Overall Resources Optimisation™

ORO™ is the concept of Megaplast describing the benefits a company will have by using and optimizing Megaplast's films for wrapping pallet loads. The usage of ORO™ is resulting in minimising the company's operational costs, maximising its total cost savings and leading to an Eco-innovation and management of resource use.



Less plastic Less waste Less CO₂ Less energy
Less warehousing Less labor cost Less green taxes



Excellent pallet
stability



Superior load
retention & safety



Consistent
Performance



At least 50% less
plastic waste



Zero film breaks
during wrapping



Low CO₂ footprint
than market average



Reduced
downtime



Total cost
savings