

# Refrigerating systems and components

Product lines overview

### **Contents**

### Refrigerating systems

Refrigeration components



### Overview of our refrigerating systems

### **Standard condensing units**





Full range of standard condensing units and silenced condensing units

## Custom condensing units & systems



Customized solutions for OEMs

#### **Monoblocks**





Monoblocks for counters

Monoblocks for cabinets

Wall-mounted and ceiling monoblocks for cold rooms

#### 100% of our refrigeration products are tested through:

Electric test, System capacity test, Instrumental functioning test, Leakage detection with mass spectrometer



### Standard condensing units range

### **Standard condensing units**

UC – UCS- UCSsa range







Valve expansion, Capillary expansion, Capillary to braze expansion

Refrigerants: R452A, R134a, R290

Applications: MHBP ( $-20 \div +10^{\circ}$ C) and LBP ( $-40 \div -20^{\circ}$ C)

Power range: 1/6 HP – 5.5 HP

### **Silenced condensing units**

Full range – certified noiselessness





Sound level 10m: 35 - 41 dBA

Refrigerant: R452A

Applications: MHBP (-20  $\div$  +10°C) and LBP

 $(-40 \div -20^{\circ}C)$ 

Power range: 1 – 6.1 HP



### **Custom condensing units & systems**







Extremely high degree of customization available: performances, dimensions, cooling fluids, layout, accessories, safety systems.



### Monoblocks for counters and cabinets

#### Monoblock range for counters

MTT 2.0



Refrigerants: R452A, R134a, R290 Applications: HBP (+2  $\div$  +8°C), MBP (-2  $\div$  +6°C) and LBP (-20  $\div$  -15°C)

Table volume: up to 4 doors

#### Monoblock range for cabinets

MTA 2.0



Refrigerants: R452A, R134a, R290 Applications: HBP (+2  $\div$  +8°C), MBP (-5  $\div$  +5°C) and LBP (-25  $\div$  -18°C)

Cabinet volume range: 700 and 1400 l



### Monoblocks for cold rooms

#### Wall-mounted monoblock range

**UMZ & UMT** 





Straddle and through-wall mounting

Refrigerants: R452A, R290

Applications: positive temperature (-5  $\div$  +5  $^{\circ}$ C), low

temperature (-25 ÷ -15°C)

Cold room volume range: 4-48 m<sup>3</sup> for positive temperature; 2-39 m<sup>3</sup> for low temperature

#### Ceiling monoblock range

UMS



Refrigerants: R452A

Applications: positive temperature (-5  $\div$  +5  $^{\circ}$ C), low

temperature (-25 ÷ -15°C)

Cold room volume range: 4-48 m³ for positive temperature; 2- 39 m³ for low temperature



### **Contents**

Refrigerating products

**Refrigeration components** 



### **Refrigeration components**

Thanks to the partnership with various refrigeration component manufacturers, MTH is able to offer a wide range of products:

Compressors

Fans

Shaded poles and electronic control fan motors

Air cooled condensers

Water cooled condensers

Filters

Thermostatic Valves

Solenoid Valves

Electronic Valves




















#### MTH Srl

Via Rivera, 92 – 10040 Almese (TO), Italia T (+39) 011 9351580 C.F./P.IVA IT-06196070012

mthsrl@mth.it mth.it