



Stucchi Quick Couplings

A constant flow of solutions

STUCCHI IN THE WORLD

ITALY - USA - CHINA - AUSTRALIA - BRAZIL - SOUTH AFRICA



Stucchi is a leading manufacturer of quick couplings, multicouplings plates and quick connect solutions

The recognized main strengths of the company are **flexibility** in the supply of standard products and the ability to develop **customized solutions**, able to satisfy partner's needs, adding value to their projects in terms of performance, safety, ease of use and environmental **sustainability**.



Hydraulic Tools



Machineries and systems related to various hydraulic equipment (machine and automation tools, powered hand tools) require high performance couplings and Stucchi can provide them.

High Pressure



Stucchi couplings are present on systems associated with high pressure applications; not only on jacks, ram or clamping devices but also on rescue equipment.

Refrigeration



Stucchi quick couplings are equipped on systems associated with vehicles refrigeration (A/C recharge) and isothermal bodies through low temperature eutectic plates.

Cooling



Machineries for cooling of systems with water or water glycol can be equipped with Stucchi quick couplings.

Chemical & Food Industry



Stucchi couplings are used in chemical applications where flow performances associated with non-spill design allows to increase system specifications and to protect the environment.

A constant flow of solutions

Experts in quick couplings since 1960

Being an Italian family-owned company, present today worldwide with branches (USA, China, Australia, Brazil) and distributors, Stucchi S.p.A. maintains its commitment to offer high quality, safe and reliable products.



The complete production process takes place in Northern Italy (Bergamo) and is certified with UNI EN ISO 9001 quality-management system.

This certification means a high level of product quality throughout the company's supply chain: beginning with raw materials certifications, ongoing improvements in production materials, production automation, and fatigue and pressure testing.

The service is completed by a punctual shipping department and a helpful after sales service.

In addition, Stucchi S.p.A. is also committed in providing its workers a safe and healthy workplace (as certified by BS OHSAS 18001:2007) as much as it is engaged in complying with international environmental management systems certification ISO 14001:2015.



**Earth
Moving**

Stucchi couplings are suitable for machines and systems related with controlling mobile equipment used in off-highway applications.



**Oil
& Gas**

In exploration, extraction, field services (upstream), storage and conveyance (downstream) of crude oil and natural gas Stucchi products are the best solutions.



Vehicles

Vehicle manufacturers appreciate Stucchi couplings for their high performances in hydraulic applications systems to connect different tools or trailers.



Agriculture

From conventional 'poppet design' profile to flat face and multicouplings, Stucchi products are present on agricultural machines and attachments.



Industry

Stucchi couplings are present on machineries and systems used for industrial manufacturing.

FLAT FACE



FIRG

Valving style: Flat face
Interchange: ISO 16028
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 2"
Operating pressure: Up to 300 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Carbon steel / Cr3



A

Valving style: Flat face
Interchange: ISO 16028
Sealing description: Nitrile NBR
Available sizes: From 1/8" to 1-1/2"
Operating pressure: Up to 420 bar
Flow rate: Up to 750 l/min
Material / Treatment:
Carbon steel / Cr3



APM

Valving style: Flat face
Interchange: ISO 16028
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 1-1/2"
Operating pressure: Up to 350 bar
Flow rate: Up to 750 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



A-HD

Valving style: Flat face
Interchange: ISO 16028
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 1/2"
Operating pressure: Up to 350 bar
Flow rate: Up to 90 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



AX

Valving style: Flat face
Interchange: ISO 16028
Sealing description: FKM (Viton®)
Available sizes: From 1/4" to 1"
Operating pressure: Up to 350 bar
Flow rate: Up to 378 l/min
Material / Treatment:
Stainless steel (AISI 316L)



FIRG-Q

Valving style: Flat face
Interchange: ISO 16028
Sealing description:
Nitrile NBR-FKM(Viton®)-EPDM-Kalrez®
Available sizes: From 1/4" to 2"
Operating pressure: Up to 300 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Internal parts in stainless steel / QPQ



FL

Valving style: Flat face
Interchange: ISO 16028
Sealing description: FKM (Viton®)
Available sizes: From 1/8" to 2"
Operating pressure: Up to 350 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Stainless steel (AISI 316L)

CASTING



SATURN 3

Valving style: Flat face
Interchange: ISO 16028
Sealing description: Nitrile NBR
Available sizes: From 1/2" to 3/4"
Operating pressure: Up to 350 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



SATURN 5

Valving style: Flat face
Interchange: ISO 16028
Sealing: Nitrile NBR
Sizes: From 1/2" to 3/4"
Operating pressure: Up to 350 bar
Flow rate: Up to 200 l/min
Material / Treatment: Carbon steel / Cr3
Connection under pressure: One side

FLAT FACE SCREW



VEP-P

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 2"
Operating pressure: Up to 600 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Carbon steel / Cr3+QPQ
Connection under pressure: Allowed



VEP-HD

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 3/4" to 1-1/2"
Operating pressure: Up to 500 bar
Flow rate: Up to 750 l/min
Material / Treatment:
Carbon steel / QPQ
Connection under pressure: Allowed



VP-P

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1-1/2"
Operating pressure: Up to 600 bar
Flow rate: Up to 750 l/min
Material / Treatment:
Carbon steel / Cr3+QPQ
Connection under pressure: Allowed

MULTICOUPLINGS



DP

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 3/4"
Operating pressure: Up to 350 bar
Flow rate: Up to 378 l/min
Material: Aluminium & carbon steel
Connection under pressure: Allowed



GR

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 1"
Operating pressure: Up to 350 bar
Flow rate: Up to 378 l/min
Material: Brass & carbon steel
Connection under pressure: Allowed



GRE

Valving style: Flat face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 1/2"
Operating pressure: Up to 10 bar
Flow rate: Up to 90 l/min
Material: Aluminium & brass

HIGH PRESSURE



A-HP

Valving style: Flat Face
Interchange: Stucchi profile
Sealing description: Nitrile NBR
Available sizes: From 1/8" to 3/8"
Operating pressure: Up to 720 bar
Flow rate: Up to 46 l/min
Material / Treatment:
Carbon steel / Cr3



IV-HP

Valving style: Ball
Interchange: With similar couplings (high pressure)
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 3/8"
Operating pressure: Up to 700 bar
Flow rate: Up to 23 l/min
Material / Treatment:
Carbon steel / Cr3

POPPET SCREW



VD

Valving style: Poppet
Interchange: ISO 14541
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1-1/4"
Operating pressure: Up to 450 bar
Flow rate: Up to 378 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



VLS

Valving style: Poppet
Interchange: With similar couplings
Sealing description: Nitrile NBR
Available sizes: From 1/2" to 1"
Operating pressure: Up to 465 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



VR

Valving style: Flat face
Interchange: With similar couplings (Rohrleitung)
Sealing description: Nitrile NBR
Available sizes: From 3/8" to 1-1/4"
Operating pressure: Up to 420 bar
Flow rate: Up to 576 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



VOF

Valving style: Poppet
Interchange: With similar couplings
Sealing description: Nitrile NBR
Available sizes: From 3/4" to 2"
Operating pressure: Up to 345 bar
Flow rate: Up to 1100 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure: Allowed



VOFX

Valving style: Poppet
Interchange: With similar couplings
Sealing description: Nitrile NBR
Available sizes: From 3/4" to 2"
Operating pressure: Up to 207 bar
Flow rate: Up to 1100 l/min
Material / Treatment:
Stainless steel (AISI 316L)
Connection under pressure: Allowed

CHECK VALVE



VUZ

Available sizes: From 1/8" to 2"
Operating pressure: Up to 400 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Carbon steel / Cr3



ACR-ACB

Valving style: Poppet
Interchange: SAE J639
Sealing description: HNBR
Available sizes: 1/4"
Operating pressure: Up to 10 bar
Flow rate: Up to 750 l/min
Material / Treatment: Brass

VEHICLE A/C

POPPET



BIR

Valving style: Poppet
Interchange: ISO 7241 'A'
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 2"
Operating pressure: Up to 350 bar
Flow rate: Up to 1000 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure:
Allowed (only PC version)



I/IP

Valving style: Poppet
Interchange: ISO 7241 'A'
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1"
Operating pressure: Up to 350 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Carbon steel / Cr3



IR

Valving style: Ball
Interchange: ISO 7241 'A' (only 1/2")
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1"
Operating pressure: Up to 300 bar
Flow rate: Up to 150 l/min
Material / Treatment:
Carbon steel / Cr3



IR-V

Valving style: Poppet
Interchange:
With similar couplings IR Series
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1"
Operating pressure: Up to 300 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Carbon steel / Cr3



IRB

Valving style: Poppet
Interchange: ISO 7241 'B'
Sealing description: Nitrile NBR
Available sizes: From 1/8" to 1"
Operating pressure: Up to 350 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Carbon steel / Cr3



IRBO

Valving style: Poppet
Interchange: ISO 7241 'B'
Sealing description: FKM (Viton®)
Available sizes: From 1/8" to 1"
Operating pressure: Up to 200 bar
Flow rate: Up to 200 l/min
Material / Treatment: Brass



IRBX

Valving style: Poppet
Interchange: ISO 7241 'B'
Sealing description: FKM (Viton®)
Available sizes: From 1/8" to 1"
Operating pressure: Up to 250 bar
Flow rate: Up to 200 l/min
Material / Treatment:
Stainless steel & brass



IFR

Valving style: Flat face
Interchange: ISO 5676
Sealing description: Nitrile NBR
Available sizes: 3/8"
Operating pressure: Up to 150 bar
Flow rate: Up to 23 l/min
Material / Treatment:
High strength carbon steel



IRC

Valving style: Poppet
Interchange: Nordic interface
Sealing description: Nitrile NBR
Available sizes: From 1/4" to 1"
Operating pressure: Up to 600 bar
Flow rate: Up to 378 l/min
Material / Treatment:
Carbon steel / Cr3
Connection under pressure:
Allowed (only PC version)



IRCX

Valving style: Poppet
Interchange: Nordic interface
Sealing description: FKM (Viton®)
Available sizes: From 1/4" to 1"
Operating pressure: Up to 300 bar
Flow rate: Up to 378 l/min
Material / Treatment:
Stainless steel (AISI 316L)



Easy Connection Under Pressure is the Stucchi solution for manual connection with residual pressure in the circuit. The male couplings have a triple valve system that allows the easy connection of couplings with internal residual pressure, in safe condition and without fluid loss.



Blow Out Prevention
Specific dimensions are fire tested and Lloyd certified in accordance with API 16D and the EUB Directive #36. For complete technical information please contact Stucchi technical support.

⚠ WARNING

A defect, a wrong choice or an improper use of products, can cause injury to persons, animals and objects. Connect under pressure products are suitable to be connected under residual (static) pressure. Never connect or disconnect with dynamic pressure (e.g. pump on). Make sure that the medium used is compatible with seal and material as indicated for each series. In case of doubt please contact Stucchi Technical Support. The interchangeability is mentioned under the assumption that the manufacturer of the considered products has not changed any dimension.

It is MANDATORY to read and closely follow the instructions.
Last updated version always apply at time of installation, see latest written Instructions on Stucchi website (www.stucchi.com) before selecting or using Stucchi products.

Stucchi S.p.A.*Headquarters*

Via della Lira Italiana, 397
24040 Pagazzano (BG) Italy

stucchigroup.com

**Stucchi USA inc.**

1105 Windham Parkway,
Romeoville
IL 60446 USA
stucchiusa.com

Stucchi (Shanghai)

Fluid Power Technology Co., Ltd
No. 5, Lane 3500, Xiupu Road
Kangqiao Industrial Park
Pudong New District
201315 Pudong Shanghai, China
stucchichina.com

Stucchi FCP Pty Ltd.

8/7-11 Rodeo Drive
Dandenong South
VIC 3175 Australia

Unit3, 22 Strathwyn Street
Brendale,
QLD 4500 Australia
stucchigroup.com/en-au

Stucchi Engates Hidraulicos Ltda.

Rua Júlio Ribeiro, 865
Bairro Vila Santana
CEP: 18080-690
Sorocaba - SP, Brazil
stucchigroup.com/br-pt

Stucchi South Africa (Pty) Ltd.

49, Mopedi Rd, Sebenza
Edenvale Po Box 8253
Edenglen 1613, South Africa
stucchigroup.com



MISTO
Carta | A sostegno della
gestione forestale responsabile
FSC® C008870



For complete technical information see www.stucchigroup.com
STUCCHI S.p.A. All right reserved. September 2022 - **STUCCHI PRODUCTS BROCHURE_EN** - 899900070