

TORO

Workman® LTX series

Utility vehicles

BUILT FOR THIS. POWER MEETS PURPOSE.

The next generation of light-duty utility vehicles is here. The new Workman LTX delivers everything that you asked for: power, comfort and elevated design.

Powered by either the Briggs & Stratton® Vanguard® 400 EFI engine or the Toro Hypercell® lithium battery system, the LTX offers standard height, lifted or extended models to help you tackle your toughest days. With abundant storage, enhanced options, optimal design and rugged reliability, you don't have to choose between strength and versatility. The Toro Workman LTX provides both, because your work deserves the best.



toro.com

F E A T U R E S

Power your way

- Select the Briggs & Stratton® Vanguard® 440 EFI petrol engine or the advanced Toro Hypercell lithium-ion battery system. Both deliver exceptional power, reliability and efficiency, so that you can tackle every job with confidence.

Steering

- An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.

Suspension

- Coil-over shocks all around the vehicle deliver greater suspension travel and adjustability, resulting in a smoother ride and minimised operator fatigue.

Endless ways to customise

- The Workman LTX gives you the flexibility to tackle any job with dozens of configuration options. Choose standard height or lifted models, extend the bed for additional hauling or add an additional row of seats for more passengers. With accessories to match, you can make your office on wheels your own.

Braking that you can count on

- Hydraulic disc brakes deliver reliable, consistent stopping power with minimal maintenance, no cable adjustments and less pedal force than traditional mechanical brakes. On lithium-powered models, an electronically controlled parking brake adds an extra layer of convenience.

Intuitive dashboard layout

- Oversized cup holders and ample storage for tools and gear. Stay in control with easy-to-reach controls and a clear LCD display. Plus, keep your devices powered on the go with integrated USB-A and C charging ports.

WORKMAN® LTX SERIES SPECIFICATIONS*

	WORKMAN LTX (GAS EFI), MODELS: 07424, 07424LT, 07424EX	WORKMAN LTX (LITHIUM), MODELS: 07425, 07425LT, 07425EX				
ENGINE/POWER SYSTEM	408 cc, air-cooled, single cylinder Briggs & Stratton® EFI petrol engine.	Two Hypercell® lithium-ion batteries standard, and an option to add an additional battery.				
ENERGY CAPACITY	N/A	4.32 kWh standard, 6.48 kWh optional. 55 V nominal; 63 V max.				
ELECTRIC MOTOR	N/A	Brushless, high-torque AC induction motor with 5.0 kW continuous power.				
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock to lock with 35 cm (13.75") diameter.					
TURNING RADIUS	Standard and lifted models: turning clearance circle: 6.3 m (20.7'), inside turning radius: 153 cm. Extended models: turning clearance circle: 9.45 m (31'), inside turning radius: 254 cm.					
BRAKES	Front and rear wheel hydraulic disc brakes.					
PARKING BRAKE	Foot pedal with accelerator pedal release.	Automatic parking brake.				
SUSPENSION	Front: modified MacPherson strut. Rear: articulating swing arm. Adjustable coil over shocks at all four wheels.					
SUSPENSION TRAVEL	Front suspension travel: 8.9 cm Rear suspension travel: 10.2 cm (4").					
FUEL CAPACITY	18.9 litres	N/A				
GROUND SPEED	16 mph governed. Speed reduction kits available.	16 mph standard, adjustable up to 24 mph. Setting of 19 mph and greater require ROPS and seat belt.				
TRANSAXLE	11.47:1 forward, 14.35:1 reverse					
GROUND CLEARANCE	Standard height models: front: 22.8 cm (9"), rear: 15.2 cm (6") Lifted models: front: 30.4 cm (12"), rear: 17.8 cm (7")					
TYRES	Standard and extended models: 20 x 8.00-10, 4-ply. Or alternate 4-ply/6-ply. Lifted models: 22 x 9.50-12, 4-ply. Or alternate 4-ply/6-ply.					
WHEELS	Standard and extended models: 25.4 cm (10") steel Lifted models: 30.5 cm (12") aluminium					
STARTER BATTERY	One 12 V starter battery	N/A				
CONTROLLER	N/A	375 A max. with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.				
CHARGER	N/A	On-board high efficiency 900 W smart charger. •AC input voltage: 100–240 VAC •AC input frequency: 50/60 Hz •Max. AC input current: 13.4 A				
INSTRUMENTS/DASH	LCD display, USB A and C power ports, headlight switch, on/off ignition key switch, horn switch, cup holders, radio holder and large storage compartments throughout dashboard.					
STARTING	Pedal or key start capability standard.	Pedal start standard.				
DIMENSIONS	Vehicle configuration	Width	Length	Height	Wheel base	
	2-seat with bed (standard height)	119.3 cm (47")	302 cm (119")	127 cm (50.2")	197 cm (77.8")	
	2-seat with bed (lifted)	119.3 cm (47")	302 cm (119")	135 cm (53.2")	197 cm (77.8")	
	4-seat with bed (extended)	119.3 cm (47")	366 cm (144")	127 cm (50.2")	290 cm (114")	
	2-seat with 1.8 m (6) flat bed (extended)	119.3 cm (47")	396 cm (156")	127 cm (50.2")	290 cm (114")	
SEAT	Line-installed bolstered bench seat, two-tone grey, with embossed Toro bullhorns on seat backs. Weight: 16 kg.					
CAB DIMENSIONS INSTALLED	Standard height models: height: 201 cm (79"), width: 142 cm (56") Lifted models: height: 208 cm (82"), width: 142 cm (56")					
WEIGHT (NOT INCLUDING BED)	2-seat: 379 kg 2-seat lifted: 390 kg 2-seat extended: 451 kg		2-seat: 386 kg 2-seat lifted: 397 kg 2-seat extended: 459 kg			
BEDS	Plastic cargo bed:	Width: 94 cm (37")	Length: 101.6 cm (40")	Height: 28 cm (11")	Weight: 55 kg	Capacity: 363 kg
	Steel cargo bed:	Width: 109 cm (43")	Length: 111 cm (44")	Height: 28 cm (11")	Weight: 89 kg	Capacity: 363 kg (800 lb)
	1.8 m (6') bed w/ sides:	Width: 117 cm (46")	Length: 183 cm (72")	Height: 28 cm (11")	Weight: 133 kg	Capacity: 363 kg (800 lb)
CANOPY DIMENSIONS INSTALLED	Standard height models: height: 191 cm (75.2"), width: 138 cm (54.3") Lifted models: height: 199 cm (78.2"), width: 138 cm (54.3")					
VEHICLE CAPACITY	2-seat with bed: 544 kg					
TOWING CAPACITY	680 kg Class 1–1.25" receiver standard.					
OPTIONAL ACCESSORIES	Canopy, folding windscreen, windscreen w/ wiper, seat kit for EX models, steel cargo bed, plastic cargo bed, 1.8 m (6') flat bed, bed sides, electric bed lift, bed racking, brush guard, brush guard w/ front receiver, rubbish bin mount, ROPS-certified cab, cab doors, light options for cab (work lights and beacon), range cage, canopy with ROPS, mirrors, brake/rear/indicator lights, back-up alarm, under-hood storage kit, ram mount ball, 12 V power point kit, all-terrain tyre kit, telematics kit. Allied accessories: drop-in beverage cart, Kimtek medical bed, Rahn Groomer					
WARRANTY	Two-year or 1,500 hour warranty. Engine warranty with Briggs & Stratton: 3-year commercial warranty +1 year after registering engine at vanguardpower.com/registration . Refer to the Operator's Manual for further details.					

* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.



toro.com

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420 USA
Phone: +(1) 952 888 8801

©2026 The Toro Company.
All rights reserved.
26-209-GB



facebook.com
youtube.com/ToroCompanyEurope
x.com/TheToroCompany



Count on it.