

HUNTER SERIES MK-X - DATA SHEET



Model	dB (C)	Ø mm	Length mm	Add. mm	Weight g *	Material	Finish	Mounting	Use
40F	23-27	39	151,5	130	≥ 185	Alloy 6068 T6, 6026 T6	Black, Hard Anodized	Thread Adapter, RASP-Lock	Air Rifle, Max. Ø 5.5 mm Bullet
40H	23-27	39	151,5	130	≥ 205	Alloy 6068 T6, 6026 T6	Black, Hard Anodized	Thread Adapter, RASP-Lock	Hornet, Max. Ø 5.5 mm Bullet
40KK	23-27	39	151,5	130	≥ 205	Alloy 6068 T6, 6026 T6	Black, Hard Anodized	Thread Adapter, RASP-Lock	Rimfire, Max. Ø 5.5 mm Bullet
50XK+	31-35	49	182	105	≥ 320	Alloy 6068 T6, 6026 T6, Stainless Steel Mesh	Black, Hard Anodized	Thread Adapter, RASP-Lock	Hunting, Standard Caliber, Several Caliber Groups
50+	34-38	49	222	145	≥ 385	Alloy 6068 T6, 6026 T6, Stainless Steel Mesh	Black, Hard Anodized	Thread Adapter, RASP-Lock	Hunting, Standard Caliber, Several Caliber Groups
55+	37-42	54	222	145	≥ 455	Alloy 6068 T6, 6026 T6, Stainless Steel Mesh	Black, Hard Anodized	Thread Adapter, RASP-Lock	Hunting, Standard & Standard Magnum Caliber, Several Caliber Groups

* Weight varies based on bore diameter of the selected caliber group and the size and weight of the thread adapter