

## 500<sup>™</sup>

High speed bagging machine

Automatic bag sealing machine  
designed for reliability, flexibility  
and optimising packaging  
throughput



# Autobag®

BRAND AUTOMATED SYSTEMS

## 500™

High speed bagging machine

Automatic bag sealing machine designed for reliability, flexibility and optimising packaging throughput



## FEATURES AND BENEFITS

- Capable of cycling at speeds up to 100 bags per min.
- Touch screen accesses operator tutorials, help and diagnostics.
- Capable of being configured for left or right-hand access.
- The system features a simple design with very few moving parts, reducing lifetime cost and improving uptime.
- Easily integrates with inline printers, counters, scales, and conveyors for semi to fully automatic bagging.
- Height adjustment and casters for ergonomics and portability.

## TYPICAL APPLICATIONS



Aerospace



Automotive



Cosmetics



Electronic



Hardware



Healthcare



Plumbing



Industrial Component

## SPECIFICATIONS

Weight	158 kg
Overall Size	H: 943 to 1196 mm W: 955 mm L: 1639 mm
Electrical	110/240 VAC, 50/60 Hz, 500 Watts (VA) max
Air Feed	5 CFM/80 psi of clean, dry air
Pass-through	125 mm max
Bag thickness	35-100 µm
Bag widths	55-300 mm
Bag lengths	70-550 mm
Weight capacity	Up to 2.2kg (with load shelf)

## SUSTAINABILITY



As a maker of flexible packaging products, we recognise the need for greater awareness and involvement in creating a more sustainable planet – from the point of manufacture to the point of disposal.

For over a decade, we have been producing environmentally responsible products for our customers. We introduced GeoTech®, a line of pre-consumer reprocessed films that forever changed the packaging industry. We have introduced innovative, lighter gauge films that reduce the amount of material required without compromising packaging performance. In addition, our machinery technology continues to evolve with new, state-of-the-art components and engineering designed to reduce energy consumption.