

touch

Touchscreen Monitor & Panel PC



Touchscreen Monitor & Panel PC



12.1"~ 27"

Comprehensive Series
Pure Flat Capacitive Touch
Screens


Rear Mounting R Series

Design: The design of glass protruding display panel surface for True-flat cabinet surface

Mounting: Supports VESA and Rear mounting brackets

Protection: IP65-rated front panel

Applications: Flexibility for mounting in tables, kiosks, or cabinets



Glass protruding display panel surface : 1.7mm.

Design for True-flat cabinet surface.

Recommended Sheet Metal Thickness : 1.5mm.


Wall Mounting L Series

Design: Aluminum alloy front bezel for stylish look

Mounting: Supports VESA

Protection: IP65-rated front panel

Applications: Flexibility for mounting in cantilever and wall



Aluminum alloy front bezel for stylish look.
A and B sides are more nice without holes.


Front Mounting F Series

Design: Compact, fan-less embedded system with aluminum alloy front bezel

Mounting: Supports VESA and Four-sided buckle for secure installation.

Protection: IP65-rated front panel

Applications: flexibility for mounting in any automatic equipment



Complete rubber seal for waterproofing.
Four-sided buckle for secure installation.

R Series Touch Monitor



Model	RTM101TRL-C	RTM133TRL-C	RTM150TRL-C	RTM156TRL-C	RTM170TRL-C
Size	10.1 inch	13.3 inch	15 inch	15.6 inch	17 inch
Active Area	216.96 x 135.6 mm	293.76 x 165.24 mm	304.1 x 228.1 mm	345.2 x 194.5 mm	337.9 x 270.3 mm
Optimal Resolution	1280 x 800 / 16:10	1920 x 1080 / 16:9	1024 x 768 / 4:3	1920 x 1080 / 16:9	1280 x 1024 / 4:3
Viewing Angle	178°H/V	170°H/V	178°H/V	178°H/V	178°H/V
Brightness	LCD panel: 400 nits; Touch Pcap: 360 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 350 nits, Touch Pcap: 315 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits
Contrast Ratio	800 : 1	1200 : 1	1000 : 1	700 : 1	1000 : 1
Backlight Life	30,000 hrs	30,000 hrs	30,000 hrs	25,000 hrs	30,000 hrs
Overall Dimensions	255 x 164 x 44 mm	334 x 222 x 48 mm	360 x 284 x 52 mm	402 x 251 x 52 mm	394 x 326 x 52 mm
Cutout Dimensions	249.9 x 158.4 mm	324.7 x 196.3 mm	348.7 x 272.7 mm	388.1 x 237.3 mm	382 x 314.5 mm
Net Weight	2.1 kg	2.9 kg	4.3 kg	3.7 kg	5.1 kg
Touch technology	PCAP, 10-point touch, 3mm tempered glass		Operating	0 ~ 50 °C (32 ~ 122°F)	
Input voltage	DC 12V, standard power adapter		Storage	-20 ~ 60°C (-4 ~ 140°F)	
Power Consumption	≤ 20W (Maximum value shown, varies by model)		Waterpproof	Front Panel IP65 for waterproof and dustproof	
I/O	1 * USB-B(Touch), 1 * VGA, 1 * HDMI(Type-A), 1 * DP, 1 * audio Phoenix terminal		Warranty	1-year warranty, support Paid Extended Warranty	
			Certificates	CE, FCC, CCC	

Model	RTM185TRL-C	RTM190TRL-C	RTM215TRL-C	RTM238TRL-C	RTM270TRL-C
Size	18.5 inch	19 inch	21.5 inch	23.8 inch	27 inch
Active Area	410.8 × 231.4 mm	377.3 × 302.1 mm	476.6 x 268.1 mm	527.6 x 297.1 mm	599.6 x 338.2 mm
Optimal Resolution	1366 x 768 / 16:9	1280 x 1024 / 4:3	1920 x 1080 / 16:9	1920 x 1080 / 16:9	1920 x 1080 / 16:9
Viewing Angle	178°H/V	165°H/V	178°H/V	178°H/V	178°H/V
Brightness	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 300 nits, Touch Pcap: 270 nits
Contrast Ratio	3000 : 1	1000 : 1	1000 : 1	1000 : 1	3000 : 1
Backlight Life	30,000 hrs	30,000 hrs	30,000 hrs	30,000 hrs	30,000 hrs
Overall Dimensions	465 x 286 x 43 mm	431 x 356 x 43 mm	532 x 324 x 43 mm	585 x 358 x 43 mm	662 x 401 x 43 mm
Cutout Dimensions	453.3 x 273.9 mm	419.48 x 344.22 mm	520.8 x 312.2 mm	573.8 x 346.1 mm	650.8 x 389.4 mm
Net Weight	5.3 kg	6.0 kg	6.6 kg	8.2 kg	9.2 kg
Touch technology	PCAP, 10-point touch, 3mm tempered glass		operating	0 ~ 50 °C (32 ~ 122°F)	
Input voltage	DC 12V, standard power adapter		storage	-20 ~ 60°C (-4 ~ 140°F)	
Power Consumption	≤ 20W (Maximum value shown, varies by model)		Anti-water	Front Panel IP65 for waterproof and dustproof	
I/O	1 * USB-B(Touch), 1 * VGA, 1 * HDMI(Type-A), 1 * DP, 1 * audio Phoenix terminal		warranty	1-year warranty, support Paid Extended Warranty	
			certificates	CE, FCC, CCC	

R Series Panel PC

System parameters refer to F-Series, contact sales for details



L Series Touch monitor



*L Series Touch Monitor

Model	RTM150TLL-C	RTM156TLL-C	RTM170TLL-C	RTM185TLL-C	RTM190TLL-C
Size	15 inch	15.6 inch	17 inch	18.5 inch	19 inch
Active Area	304.1 x 228.1 mm	345.2 x 194.5 mm	337.9 x 270.3 mm	410.8 x 231.4 mm	377.3 x 302.1 mm
Optimal Resolution	1024 x 768 / 4:3	1920 x 1080 / 16:9	1280 x 1024 / 4:3	1366 x 768 / 16:9	1280 x 1024 / 4:3
Viewing Angle	178°H/V	178°H/V	178°H/V	178°H/V	165°H/V
Brightness	LCD panel: 350 nits, Touch Pcap: 315 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits
Contrast Ratio	1000 : 1	700 : 1	1000 : 1	3000 : 1	1000 : 1
Backlight Life	30,000 hrs	25,000 hrs	30,000 hrs	30,000 hrs	30,000 hrs
Overall Dimensions	352 x 276 x 49 mm	391 x 241 x 49 mm	385 x 318 x 49 mm	457 x 277 x 49 mm	423 x 348 x 49 mm
Installation Size	100x100mm M4 VESA	100x100mm M4 VESA	100x100mm M4 VESA	100x100mm M4 VESA	100x100mm M4 VESA
Net Weight	4.5 kg	3.8 kg	5.4 kg	5.7 kg	6.3 kg
Touch technology	PCAP, 10-point touch, 3mm tempered glass		operating	0 ~ 50 °C (32 ~ 122°F)	
Input voltage	DC 12V, standard power adapter		storage	-20 ~ 60°C (-4 ~ 140°F)	
Power Consumption	≤ 20W (Maximum value shown, varies by model)		Anti-water	Front Panel IP65 for waterproof and dustproof	
I/O	1 * USB-B(Touch), 1 * VGA, 1 * HDMI(Type-A), 1 * DP, 1 * audio Phoenix terminal		warranty	1-year warranty, support Paid Extended Warranty	
			certificates	CE, FCC, CCC	

Model	RTM215TLL-C	RTM238TLL-C	RTM270TLL-C	
Size	21.5 inch	23.8 inch	27 inch	
Active Area	476.6 x 268.1 mm	527.6 x 297.1 mm	598.6 x 337.2 mm	
Optimal Resolution	1920 x 1080 / 16:9	1920 x 1080 / 16:9	1920 x 1080 / 16:9	
Viewing Angle	178°H/V	178°H/V	178°H/V	
Brightness	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 250 nits, Touch Pcap: 225 nits	LCD panel: 300 nits, Touch Pcap: 270 nits	
Contrast Ratio	1000 : 1	1000 : 1	3000 : 1	
Backlight Life	30,000 hrs	30,000 hrs	30,000 hrs	
Overall Dimensions	524 x 316 x 49 mm	577 x 349 x 49 mm	654 x 393 x 49 mm	
Installation Size	100x100mm M4 VESA	100x100mm M4 VESA	100x100mm M4 VESA	
Net Weight	6.7 kg	8.1 kg	9.0 kg	
Touch technology	PCAP, 10-point touch, 3mm tempered glass		operating	0 ~ 50 °C (32 ~ 122°F)
Input voltage	DC 12V, standard power adapter		storage	-20 ~ 60°C (-4 ~ 140°F)
Power Consumption	≤ 20W (Maximum value shown, varies by model)		Anti-water	Front Panel IP65 for waterproof and dustproof
I/O	1 * USB-B(Touch), 1 * VGA, 1 * HDMI(Type-A),		warranty	1-year warranty, support Paid Extended Warranty
	1 * DP, 1 * audio Phoenix terminal		certificates	CE, FCC, CCC

L Series Panel PC

System parameters refer to F-Series, contact sales for details



*L Series Panel PC

F Series Touch monitor



Model	RTM121TF-C	RTM150TF-C	RTM156TF-C	RTM170TF-C	RTM215TF-C
Size	12.1 inch	15 inch	15.6 inch	17 inch	21.5 inch
Active Area	246.1 x 184.6 mm	304.1 x 228.1 mm	345.2 x 194.5 mm	337.9 x 270.3 mm	476.6 x 268.1 mm
Optimal Resolution	1024 x 768 / 4:3	1024 x 768 / 4:3	1920 x 1080 / 16:9	1280 x 1024 / 4:3	1920 x 1080 / 16:9
Viewing Angle	170°H/V	178°H/V	178°H/V	178°H/V	178°H/V
Brightness	LCD Panel: 500 nits, Touch Pcap: 450 nits	LCD Panel: 350 nits, Touch Pcap: 315 nits	LCD Panel: 250 nits, Touch Pcap: 225 nits	LCD Panel: 250 nits, Touch Pcap: 225 nits	LCD Panel: 250 nits, Touch Pcap: 225 nits
Contrast Ratio	1200 : 1	1000 : 1	700 : 1	1000 : 1	1000 : 1
Backlight Life	50,000 hrs	30,000 hrs	25,000 hrs	30,000 hrs	30,000 hrs
Overall Dimensions	293 x 231 x 50 mm	353 x 277 x 50 mm	392 x 242 x 50 mm	386 x 319 x 50 mm	525 x 317 x 50 mm
Cutout Dimensions	285 x 223.6 mm	345.4 x 269.4 mm	384.8 x 234 mm	378.8 x 311.3 mm	517.4 x 308.9 mm
Net Weight	3 kg	4.5 kg	4 kg	5.5 kg	6.8 kg
Touch technology	PCAP, 10-point touch, 3mm tempered glass		operating	0 ~ 50 °C (32 ~ 122°F)	
Input voltage	DC 12-24V (2-PIN Phoenix terminal)		storage	-20 ~ 60°C (-4 ~ 140°F)	
Power Consumption	≤ 30W (Maximum value shown, varies by model)		Anti-water	Front Panel IP65 for waterproof and dustproof	
I/O	1 * USB-B(Touch), 1 * VGA, 1 * HDMI(Type-A), 1* DP		warranty	1-year warranty, support Paid Extended Warranty	
			certificates	CE, FCC, CCC	

F Series Panel PC



Processor	Elkhart Lake J6412	Tiger Lake i3-1115G4	Tiger Lake i5-1135G7	Tiger Lake i7-1165G7	Ice Lake i5-1035G1	Ice Lake i7-1065G7
Core Count	Quad-core	Dual-core	Quad-core	Quad-core	Quad-core	Quad-core
Frequency	2.00 GHz, Up to 2.60GHz	3.00 GHz, Up to 4.10GHz	2.40 GHz, Up to 4.50GHz	2.80 GHz, Up to 4.70GHz	1.00 GHz, Up to 3.60 GHz	1.30 GHz, Up to 3.90 GHz
Cache	1.5 MB	6 MB	8 MB	12 MB	6 MB	8 MB
TDP	10W	15W Default				
Memory	DDR4 8GB Default, Up to 32GB	DDR4 8GB Default, Up to 64GB			DDR4 8GB Default, Up to 32GB	
Storage	256 GB SSD Default, Up to 1TB					
5/4G	Support 5G [Optional]	Support 5G / 4G, with 1*nano-SIM Card Slot [Optional]			Support 5G / 4G [Optional]	
WIFI	Support WIFI + BT [Optional]					
Ethernet	2 * Intel®GBE LAN Chip (10/100/1000 Mbps, RJ45)				2 * Intel®GBE LAN Chip (10/100/1000 Mbps, RJ45), [Optional: 4 LAN RJ45]	
USB	3*USB3.0, 3*USB2.0	6 * USB3.0			4 * USB3.0, 2 * USB2.0	
HDMI Output	2 * HDMI (Type-A): max resolution up to 4096 x 2160 @ 30 Hz				1 * HDMI (Type-A): max resolution up to 4096 x 2160 @ 30 Hz	
Serial Port	1 * RS485 [Optional: RS232, GPIO], 3 * RS485 / RS232 (by DIP Switch)				1 * RS485 [Optional: GPIO], 3 * RS485 / RS232 (by DIP Switch)	
Operating	Windows 10/11 64bit, Linux					
Power Supply	DC 9~36V (3P-5.08 Phoenix Connector)				DC 12~24V (3P-5.08 Terminal Block)	

any

上海钛众电子科技有限公司

Anytouch Technologies Co., Ltd.

Shanghai HO: 4th Floor, No. 55, Lane 123, Shenmei Road, Pudong New Area, Shanghai, China.

Zhejiang R&D: No.3088 Century Avenue, Luoxing Street, Jiashan County, Jiaxing, Zhejiang, China.

Contact: +86 021-58361091; +86 021-58361092

E-mail: sales@anytouch.cn

anytouch



www.anytouch.cn