



## Laser receiver ACCEPTOR M

Sturdy laser receiver with easy-to-view display for use with construction machinery.

When used with a rotating laser, the new Nedo ACCEPTOR M excavator receiver accurately shows whether the excavator blade is above, at or below the required height. Large, bright LEDs make it easy to view the display from the excavator cab.

The switchable tilt compensation accounts for tilting of the dipper arm up to an angle of 30°. In this way the ACCEPTOR M reliably and accurately shows the position of the excavator blade in relation to the required height.



### Features:

- Robust excavator receiver for all rotating lasers with red laser beam
- Large detector field with a length of 190 mm
- 220° reception angle for reliable reception of the laser beam
- Very sturdy design
- Splashproof and dustproof in accordance with IP 66
- Firmly attached to the dipper arm by means of 12 very strong magnets
- Rubber studs to prevent slipping
- 3 precision levels with resolutions of 4 mm, 8 mm or 12 mm
- Very bright LEDs for easy viewing from the cab
- Tilt compensation up to 30° for greater precision even when the dipper arm is inclined
- Deactivatable signal tone
- Transport case included
- Suitable for all rotating lasers with wavelengths from 600 nm to 780 nm



Ref.-No.	430 335
Accuracy	± 4 mm, ± 8 mm und ± 12 mm
Working range	Ø 1000 m (depends on laser)
Length of detector field	190 mm
Reception angle	220°
Protection class	IP 66
Operating temperature	-10°C to +50°C
Power supply	1 x 1.5 V mono-cell
Operation duration	approx. 45 h

Technical data subject to change



# Nedo®

Precise surveying and measuring

**Nedo** GmbH & Co. KG  
Hochgerichtstrasse 39-43  
D-72280 Dornstetten

Phone +49 (0) 7443 24 01-0  
Fax +49 (0) 7443 24 01-45

info@nedo.com www.nedo.com