


R230 | Biotrituratore






7-9
m³/h*



230 x 110
AxB mm



110
Ø max.* mm



Benzina + Avviamento elettrico
Petrol + Electric start
Essence + Démarreur électrique
Benzinmotor + Elektroanlasser
Gasolina + Arranque eléctrico
Benzinmotor + Elektrische start
Benzín + Elektrické startování
Benzinski + Elektro start
Benzyna + Rozruch elektryczny
Бензиновым + Электростартом



HONDA GX630
hp21



l l/h
10 4,8



OBS
On Board System



	 0 000000	VARIANT -M				OBS	 m ³ /h	 A x B x C mm	 mm	 kg
	R230BH21SN	R230BH21SN-M		HONDA GX630 hp21			7 - 9	1860/2450 x 750 x 1540/1850	1030	615 x 585 540/605



* Materiale in entrata - Dato dipendente dal tipo di materiale e dalle condizioni di lavoro. / Input material - Data depending on the kind of material and working conditions. / Matière entrante - Donnée dépendante du type de matériel et des conditions de travail. / Eingangsmaterial - Daten, die von der Art des Materials und den Arbeitsbedingungen abhängen. / Material entrante - Dato que depende del tipo de material y de las condiciones de trabajo. / Ingangsmateriaal - Deze gegevens zijn afhankelijk van het soort materiaal en de werkomstandigheden. / Vstupní materiál - Záleží na druhu materiálu a pracovních podmínkách. / Ulazni materijal - Ovisno o vrsti materijala i uvjetima rada. / Materiał wsadowy - W zależności od rodzaju materiału i warunków eksploatacji. / Входной материал - Это зависит от вида материала и от условий труда.



R230BH21SN
HONDA GX630 hp21
+ **OBS** - On Board System



750 mm

GENTLE
LAWN
STEERING

