

G SERIES

We track and protect your valuable assets !



Contact Us



GL100

GM100

NETWORK

Global 4G with 2G fallback wider coverage and lower latency . Reuse .

BANDS

4G: B1 B2 B3 B4 B5 B7 B8 B12 B13 B20
B28 B39 B40
2G: B2 B3 B5 B8

BATTERY TYPE

2500mAh Li-Ion

BATTERY LIFE

30 Days @ Every 15 min GNSS ON
45 Days @ Every 15 min Cell ID and WiFi

DIMENSION

121mm x 61mm x 8mm

CERTIFICATION

CE FCC

Global CatM1 with 2G fallback wider coverage

CatM1 :B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25
/B26*/B27/B28/B66/B71/B85
2G: 850/900/1800/1900MHz

2500mAh Li-Ion

30 Days @ Every 15 min GNSS ON
45 Days @ Every 15 min Cell ID and WiFi

121mm x 61mm x 8mm

CE FCC DOS -160G

GLOBAL CONNECTIVITY

Global network supported

MULTIPLE POSITIONING

CELL ID WiFi SCAN and GNSS

BLUETOOTH EXTENSION

PAIR with up to 100 Bluetooth sensors

BATTERY TYPES

Rechargeable Li-Ion

MULTIPLE SENSORS

Temperature , Humidity , light , motion

ULTRA THIN

8mm Thickness

GOODS TRACKER SOLUTIONS

We Track and Protect Your Valuable Assets

G SERIES

We track and protect your valuable assets !



Contact Us



GL600

GL610

NETWORK

Global 4G with 2G

Global 4G ONLY

Operation Temperature

-30°C to 70°C

20°C to 60°C

BATTERY TYPE

2000mAh NI-MH

3400mAh AA Alkaline

BATTERY LIFE

20 Days @ Every 15 min GNSS ON
30 Days @ Every 15 min Cell ID and WiFi

60 Days @ Every 15 min GNSS ON
90 Days @ Every 15 min Cell ID and WiFi

DIMENSION

109mm x 65mm x 23mm

109mm x 65mm x 23mm

CERTIFICATION

CE* FCC*

CE* FCC*

GLOBAL CONNECTIVITY

Global network supported

BLUETOOTH EXTENSION

PAIR with up to 100 Bluetooth sensors

MULTIPLE SENSORS

Temperature , Humidity , light , motion, Air Pressure

MULTIPLE POSITIONING

CELL ID WIFI SCAN and GNSS

BATTERY TYPES

Non-Li Alkaline and NI-MH Replaceable

Temperature Spec

NIST Traceability
High Accuracy
External Probe Option

GOODS TRACKER SOLUTIONS

We Track and Protect Your Valuable Assets

A SERIES

We track and protect your valuable assets !



GLOBAL CONNECTIVITY Global network supported	BLUETOOTH EXTENTION PAIR with up to 100 Bluetooth sensors	MULTIPLE SENSORS light , motion
MULTIPLE POSITIONING CELL ID WIFI SCAN and GNSS	BATTERY TYPES Non-chargeable Battery	ROBUST IP68

Contact Us



AL300

NETWORK

Global 4G with 2G fallback wider coverage and lower latency .

BANDS

4G: B1 B2 B3 B4 B5 B7 B8 B12 B13 B20 B28 B39
B40
2G: B2 B3 B5 B8

BATTERY TYPE

7000+ mAh Li-SOCl2

BATTERY LIFE

7 Years @ 1 ping per day

DIMENSION

138mm x 72mm x 22mm

CERTIFICATION

CE FCC ATEX

AM300

Global CatM1 with 2G fallback wider coverage

CatM1 :B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25 /B26*/B27/B28/B66/B71/B85
GSM: 850/900/1800/1900MHz

7000+ mAh Li-SOCl2

7 Years @ 1 ping per day

138mm x 72mm x 22mm

ASSETS TRACKER SOLUTIONS

We Track and Protect Your Valuable Assets

V SERIES

We track and protect your valuable assets !



Contact Us



VL300

VM300

VG300

NETWORK

Global 4G with 2G.

BANDS

4G: B1 B2 B3 B4 B5 B7 B8 B20 B28 B66
2G: B2 B3 B5 B8

Global CatM1 with 2G

2G GSM

POWER SUPPLY

9V-90V

9V-90V

9V-30V

SLEEP

< 0.5 mA

< 0.5 mA

<3mA

DIMENSION

82mm x 40mm x 18mm

82mm x 40mm x 18mm

82mm x 40mm x 18mm

INTERFACE

VCC GND IGN RELAY DI DO
TX RX RS232

VCC GND IGN RELAY DI DO
TX RX RS232

VCC GND IGN RELAY

GLOBAL CONNECTIVITY
Global network supported
2G, 4G and CatM1

MULTIPLE POSITIONING
CELL ID WIFI SCAN and
GNSS

BLUETOOTH EXTENTION
PAIR with external BLE Sensors
(Panic Button, Door Sensor)

DATA MEMORY
30,000 Message

MULTIPLE INTERFACES
TX RX 1 WIRE DI DO

HIGH GAIN ANTENNA

VEHICLE TRACKER SOLUTIONS

We Track and Protect Your Valuable Assets

V SERIES

We track and protect your valuable assets !



GLOBAL CONNECTIVITY Global network supported 2G, 4G and CatM1	BLUETOOTH EXTENTION PAIR with external BLE Sensors (Panic Button, Door Sensor)	MULTIPLE INTERFACES TX RX 1 WIRE DI DO Dual Bands L1&L5 GNSS
MULTIPLE POSITIONING CELL ID WIFI SCAN and GNSS	DATA MEMORY 30,000 Message	LoRa BackUp

Contact Us



VL350

VL360*

NETWORK

LTE Cat.1 4G with 2G.

LTE 4G Cat1 with 2G

BANDS

4G: B1 B2 B3 B4 B5 B7 B8 B20 B28 B66
2G: B2 B3 B5 B8

CatM1 :B1/B2/B3/B4/B5/B8/B12/B13/B14/B18/B19/B20/B25
/B26*/B27/B28/B66/B71/B85
GSM: 850/900/1800/1900MHz

POWER SUPPLY

9V-90V

9V-90V

SLEEP

< 1 mA

< 1 mA

DIMENSION

67mm x 60mm x 21mm

67mm x 60mm x 21mm

HIGH-LIGHTS

LoRa as BackUp transmit

LoRa as BackUp transmit
High Accuracy Dual Bands GNSS . <1 meter
Compatible with FMC130*

VEHICLE TRACKER SOLUTIONS

We Track and Protect Your Valuable Assets

E SERIES

We track and protect your valuable assets !



Contact Us



EH4

EM2

NETWORK

BLE 5.0.

BLE 5.0

SCENARIOS

Temperature Logger

Motion / Door Sensor

BATTERY LIFE

3 Years

3 Years

RANGE

-30°C / +80°C

-20°C / +60°C

DIMENSION

82mm x 40mm x 18mm

70mm x 46mm x 21mm

SENSORS

Temperature Humidity

Accelerometer Hall

GLOBAL CERTIFICATION
FCC/CE/RoHS/REACH/

LONG BATTERY LIFE

BLUETOOTH EXTENSION
PAIR with G A V series tracker devices

DATA MEMORY

MULTIPLE SENSORS
Temperature Humidity Motion Hall

BLE SENSORS

We Track and Protect Your Valuable Assets

SDK VERSION

We track and protect your valuable assets !



Contact Us



NETWORK

Global network , 2G 3G 4G NB-IoT and CatM1

SCENARIOS

Assets , Personal and Vehicle

POSITIONING

GNSS LBS WIFI and BLE

SENSORS

Motion , Temperature , Humidity , Ambient light , pressure

INTERFACE

DI DO AI CAN RS232 485 AUDIO

CERTIFICATION

HARDWARE DESIGN

FIRMWARE SDK

MANUFACTURE

BUILD YOUR OWN TRACKER

We Track and Protect Your Valuable Assets