FLOWATCH® SILENCE DESIGN DT20 |

The quietest trunking pump in the world! A complete kit, with a quality trunking and all the accessories needed for installation! For air conditioners up to 20kW / 68000BTU.






















Suction: 5/7 mm - supplied Discharge: 6/9 mm - not supplied

Hose diameter

SPECIFICATIONS

Flowrate max	20 l/h
Suction head max	3 m
Discharge head max	10 m
Electrical power	3W
Voltage	Univolt 100-240V 50/60Hz
Alarm	NC
Noise level	Ú×
Protection rating	IP24
Operating cycle*	100%
Power / alarm cable	1.6 m
Trunking dimensions	80 x 60 mm
Certifications	CE, UKCA, EAC

^{*} The pump is able to run 100% of the time if necessary.



BENEFITS



Extreme silence

The trunking pump

THE MOST SILENT IN THE WORLD!



FLOWATCH® SILENCE DT20 included

Quite simply, the new standard on the market.

New Technology

Ultra-low power consumption, unrivalled silence, exceptional reliability... Tested and approved!

Very low power consumption

Only 3W power consumption, during operation only!



Custom-made pump casing

For easy installation and perfect integration into the trunking.



New trunking

A market-standard trunking system that's aesthetically pleasing, easy to install and comes with a wide range of accessories.



Stop siphoning included

Allows to avoid all risk of negative discharge and to secure the pump functioning over time.



Plug & Play connectors

Make installation and maintenance easier.

CONTENTS

Trunking with elbow - Finishing gasket - Finishing ceiling plate - Pump in absorber bracket -Stop Siphoning - Reservoir with air-vent tube - Power / alarm cable - Inlet tube - Suction tube 0.25m -Screws and rawlplugs

