









All PACO hooked screens are optimized for the job in hand - from choice of materials, through design to finishing quality. Regardless of whether side or end tensioned, they always provide reliable performance coupled with long lifetimes. They can be easily re-tensioned, efficiently cleaned and quickly exchanged.

For example: popular hook styles

Hook B 1

Hook bent parallel. Hook opening angle 10-20°



Hook B 2

For fine screens with a wire thickness of max. 0.9 mm.

Hook opening angle according to customer specifications.



Hook B3

Opening angle 30-40°, suitable for end and side tensioning. Bending radius 4-6 mm. For coarse screens with a wire thickness of 2.5 mm.



Other hook types and custom versions on request.

Your own specific **PACO** hooked screen

screen to your own individual requirements, with one of our specialist engineers. PACO has developed a special request form. You can download it and print it out from It helps you to clearly present your needs and www.paco-online.com

To assist you with the specificiation of a hooked provides a practical basis for futher discussions

From New Screens to Reconditioned Screens:

PACO's Comprehensive Screen Service



Screening is one of the fundamental processing technologies in almost all industries. Consequently, there is a large demand for new screens – just as there is for reconditioning and retensioning used screens. To meet these demands, PACO has ramped up its working capacities as well as its range of services.

House to house service

We will arrange to pick up your used screen and return it to you after processing. The prices for this service are very competitive and based on



distance (see PACO Screen Service Map). On the basis of the wear pattern, we can help you find the root cause of any damage or premature wear and provide assistance in optimizing your screening process.

Perfect tensioning technology

For screen tensioning, PACO uses optimized production equipment and precision measuring technology. The metal wire cloths are absolutely uniformly tensioned in all directions. This provides particularly high levels of rigidity that optimally transmit the screening vibrations and ensure increased productivity.

Round screen with up to 3000 mm diameter!

An exclusive PACO screening offer is the remeshing of round screens with a diameter of up to 3000 mm! It goes without saying that the PACO transport service that collects

PRODUCTS





PACO Screen Service Map

For the reconditioning of used screens, PACO offers an all-round service from door to door.

The competive prices for the collection and re-delivery of screens is based on distance. The PACO Screen Service Map shows the corresponding distance zones. We can provide you with the exact prices on request under

E-Mail: info@paco-online.com

Telephone: +49 (0) 66 63 - 97 8 - 0 Telefax: +49 (0) 66 63 - 91 91 16





