DCGGC WORLD CLASS TOUCH DISPLAY COMPUTERS WEB TERMINALS PANEL PCs and MONITORS





Standard & Customiseable Touch Display Computers



Touch Display Computers Sleek and modern design, high performance

DISPLAY

Designed in-house

- 4.3" to 49.0" range
- Proprietary Ultra-wide viewing angle technology (UWAT) or IPS
- Portrait or landscape modes
- 24-bit colour depth clear and vibrant colours
- High brightness backlights
- Industrial temperature range
- Long lifetime

TOUCH

- Projected Capacitive Touch
- State of the art, in-house developed
- specifically for our DLOGIC modules
- Latest technology touch sensor
- Water and moisture support
- Glove touch support
- Pen support

ELECTRONICS

- NXP i.MX series technology
- Industrial grade components
- Galvanic isolated interfaces
- Input power protection
- High performance, wide input voltage
- Battery backed real-time clock
- Conforms to various ISO, UL, CE standards









INTRODUCTION

STANDARD COMPUTER PLATFORM TOUCH DISPLAY MONITORS VANDAL RESISTANT & OPTICAL BONDING

The i.MX 8 series of applications processors,

architecture-including combined advanced graphics, imaging, machine vision, audio, voice,

platform, is a feature and performance-scalable

multicore platform based on the Arm® Cortex®

part of the EdgeVerse™ edge computing

video and safety-critical applications.

NEW NXP i.MX8M

MECHANICAL INTEGRATION

APPLIC



Product: DL-DM2380-Marine Application: Cargo Ship Control Room



Product: DL-DM2700-4K Application: Medical Diagnostics Machine

Product: Customised 49" 1080x1920 Touch Monitor Application: Vending Machine



ASK US NOW

ABOUT US

APPLICATIONS & QUALITY

LICATIONS

SOFTWARE PLATFORMS DEVELOPMENT KIT & BSP



STANDARD PRODUCT LIST

Clearbond® Optical Bonding



DLOGIC models are available with our proprietary ClearBond ® optical bonding technology.

This removes any unwanted reflection of light between the display and touch sensor while ensuring there is no possibility for dust and dirt to get in between the cover lens, touch sensor and TFT display surfaces.

This is particularly important for equipment designed for outdoor use to avoid reflection from direct sunlight as well as protecting from dirt, dust, moisture, shock and vibration.

FEATURES

IMPROVES VIEWABILITY IN ALL CONDITIONS

INCREASES RUGGEDNESS

IMPROVES RESISTANCE TO SHOCK, IMPACT & VIBRATION

RESISTANT TO DUST, DIRT AND MOISTURE

Largest size currently in production utilsing our ClearBond[™] optical bonding technology

Application : Outdoor Vending

Product series : DL-DM4900-HDMI-SGF

- 49.0" 1920 x 1080 IPS TFT, Optical Bonded
- High-brightness backlight, 700cd/m2
- 8mm thick, physically hardened safety glass
- Capacitive Touch USB

Interfaces :

LICATIONS

- Display Port to LVDS 2-ch
- Backlight control
- Customised mechanical housing

APPLICATIONS & QUALITY

SOFTWARE PLATFORMS DEVELOPMENT KIT & BSP

ASK US NOW



ABOUT US

DLOGIC.COM 9

STANDARD

PRODUCT LIST

and resources on your core product development

Product: DL-DM700x-RV Application: Automotive Recreational Vehicle (RV) auxillary controller

- Front mounted 7" Touch Display Computer
- Spring-Loaded Blind Mounting
- Easy Installation and Maintenance





Customers main metal housing

Rear mounting frame

APPLICATIONS & QUALITY

LICATIONS

SOFTWARE PLATFORMS N DEVELOPMENT KIT & BSP

LONG-LIFE SUPPLY

GUARANTEE

STANDARD PRODUCT LIST

ABOUT US

ASK US NOW

More product examples

Product: DL-DM1010q (i.MX8M Plus Quad Arm Cortex A53) **Application: Industrial Web Terminal**

Web terminal based on HTML5 and Chromium browser. Numerous application possibilities.

NEW! 7", 10.1", 15.6", 18.5", 21.5", 23.8", 27.0" Web Terminals



Product: DL-DM1010q-IO (i.MX8M Plus Quad Arm Cortex A53) **Application: Pneumatic Tube Delivery System**



Periperals include;

- 2 Serial Ports Stereo Audio
- microSD Card
- Integrated overvoltage protection
- 2 Ethernet Ports Up to 4 USB 2.0
- 2 RS485
- Power Input from 10V to 32V
- Lockable Phoenix Connectors

INTRODUCTION

STANDARD COMPUTER PLATFORM

TOUCH DISPLAY MONITORS

VANDAL RESISTANT & OPTICAL BONDING MECHANICAL INTEGRATION

APPLIC

Product: DL-DM700x-USB (i.MX6DL ARM CORTEX A9) Application: Laboratory equipment

- 7.0" 1024x600 IPS TFT Display
- Optically bonded Projected Capacitive Touch panel
- 4 port USB, Ethernet
- 20 pin peripheral interface connector



Product: DL-DM1010x-MARINE (i.MX8M Dual Arm Cortex A53) Application: Marine System Controller

Capacitive high-bright touch display offers impressive daylight visibility with crisp graphic detail and elegant touch sensitivity, NMEA2000 compatible.



ASK US NOW

APPLICATIONS & QUALITY

LICATIONS

SOFTWARE PLATFORMS DEVELOPMENT KIT & BSP

STANDARD PRODUCT LIST

ABOUT US

Software Platform

The DLOGIC value proposition combines world class software and hardware in a ready to install product guaranteeing quick time to market and therefore excellent return on investment for your project.

