



TWO-WHEEL TRACTOR

agria 3400

Base unit

Benefits at a glance:

- Perform various jobs due to turnable handle bar
- Comprehensive equipment options designed to meet requirements
- Lockable differential axle makes the machine controllable and easily reversible
- PTO shaft speed independent of gear allows gradual adaptation to working conditions
- Attachment coupling by Agria: Change attachments easy and fast
- KL-models: Single wheel steering brake clutches for sensitive cornering without speed increasing



TECHNICAL SPECIFICATIONS

	agria 3400
Article number	3400 822
Engine	Kohler Command PRO CH395 1-cylinder-4-stroke petrol 7.1 kW (9.7 HP)
Fuel capacity	7.0 litres
Gear	4-stroke reverse gear in differential version, with lock, 4 forward/4 backward*
Speeds	F/B*: 1.0; 1.9; 3.25 and 7.1 km/h
Fast gear with 16.9 km/h**	—
Steering	
Single-wheel steering brake clutches	—
Standard equipment	
Vertically and laterally adjustable handlebar without tools	•
Handlebar turnable by 180°	•
Hand start	•
Electric start	option
Hitch	•
Generator 12 V	150 Watt
Operation hour counter	•
Operation and locking brake	•
Hydroelectric station hubs	•
Front support leg	•
Weight (without wheels)	approx. 106 kg

* 3B in case of handlebar position two-wheel tractor

** in position of handlebar two-wheel tractor only for transport purposes

Product illustrations partly do not correspond to the delivery version and may contain accessories.



Handlebar turnable by 180°



Handlebar can be easily laterally adjusted



Attachment coupling by Agria: Change attachments easy and fast



Stand support makes changing attachments and storing the machine easier



Robust steering brake clutch for easy steering



Additional fixture for towed attachments e.g. ploughs

LOW-VIBRATION OPERATION



Verified by certified vibration measurements

Ex.: Stone buri-er:
2.10 a_{hd} according to DIN EN 709
(uncertainty K of a_{hd}: 0.15)

Further technical data available on request.

ATTENTION

The base models of this type are supplied without wheels. Please order the wheels separately.



agria 3400 KL	agria 3400 D E-Start	agria 3400 D E-Start, Fast speed	agria 3400 KL D E-Start
3400 837	3400 415	3400 416	3400 435
Kohler Command PRO CH395 1-cylinder-4-stroke petrol 7.1 kW (9.7 HP)	Yanmar L100V 1-cylinder-4-stroke Diesel engine 6.8 kW (9.2 HP)		
7.0 litres	4.7 litres		
4-shift reverse gear 4 forward/4 backward*	4-stroke reverse gear in differential version with lock, 4 F/4 B*		4-shift reverse gear 4 forward/4 backward*
F/B*: 1.0; 1.9; 3.25 and 7.1 km/h	F/B*: 1.0; 1.9; 3.25 and 7.1 km/h	F/B*: 1.0; 1.9; 3.25 and 16.9 km/h	F/B*: 1.0; 1.9; 3.25 and 7.1 km/h
–	–	•	–
•	–	–	•
•	•	•	•
•	•	•	•
option	•	•	•
•	•	•	•
150 Watt	180 Watt	180 Watt	180 Watt
•	•	•	•
•	•	•	•
•	•	•	•
•	•	•	•
approx. 133 kg	approx. 147 kg	approx. 147 kg	approx. 175 kg

- Standard equipment
- not available

TWO-WHEEL TRACTOR

agria 3400

Highlights attachments

The two-wheel tractors of the series **agria 3400** offer you a large selection of attachments. Here you will find the latest innovations as well as classics and must-haves.



HOEING AND TILLING ATTACHMENT

The combination of two-wheel tractor with hoeing and tilling attachments makes a very good match. With the robust and specially shaped hoeing tools, you always get a uniform working result in soil or seedbed tillage.

The offset arrangement of the blades allows a smooth operation even on heavily compressed or uneven soils. That's why this team has been one of the absolute must-haves in gardening and landscaping for decades.



WEED BRUSH WK 70

The advantages of mechanical weed removal are obvious: in addition to the visible results immediately after application, harmful herbicides can also be dispensed with in the interests of the environment.

The weed brush WK 70 removes weeds quickly and effectively with its wide brush. With a variety of brushes and many adjustment possibilities you get a clean working result on all surfaces.



STONE BURIER

The stone burier is a special construction in which the rotavator shaft rotates reversely to the rotating direction of the tractor wheels. The soil cut out by the rotavator blades is thrown against metal railings whereby stones and rough plant rests are separated from the fine soil and subsequently is covered by the soil.

You get a finely crumbled seed bed free of stones and other unwanted materials.



agria 3400
with stone burier

Remote-controlled devices

Hand-held tool carriers

Two-wheel tractors



agria 3400
with Levelling triple rake



agria 3400
with weed brush B100

Mowers

Weed brushes
Sweepers

ACCESSORIES

On the next page you will find a wide range of accessories and selection of accessories and a selection of attachments. Do you need advice? Contact us!

Hoeing

TWO-WHEEL TRACTOR

agria 3400

Attachments Soil cultivation

Hoeing and tilling attachment



Working width / weight:

**70 cm rough / 31 kg; 70 cm fine / 30 kg
80 cm rough / 31 kg; 80 cm fine / 33,5 kg**

The hoeing and tilling attachment can be used to prepare a finished seed bed or planting bed in a single operation. It can also bring organic material (for example for manure) into the soil.

Stone burier




Working width / weight:

70 cm / 128 kg

The stone burier separates stones and rough plant rests from the fine soil and buries them under. So you get a seed bed free from annoying materials and finely crumbled.

Power harrow



Working width / weight:

**75 cm / 117 kg; 90 cm / 122 kg
100 cm / 128 kg**

After ploughing with a power harrow, larger soil clods are shredded, soil is loosened and leveled at the same time.

Lawn sowing machine



Working width / weight:

90 cm / 29 kg; 100 cm / 30 kg

While the power harrow shreds and levels the soil, the lawn sowing machine simultaneously sows the seed mixture – all in one working step.

Levelling triple rake



NEW!

Working width / weight:

146 cm / 120 kg

The levelling triple rake distributes, crushes and levels the soil in one step. The three individual rakes are unique on the market and achieve a particularly clean planum.

CREATING IDEAL CONDITIONS FOR GROWTH

There are just a few things that are more annoying than to see hard placed plants wither. Besides the costs for a new sowing, the work done in vain often hurts much more.

In order to form the basis for successful growth, the right soil cultivation is essential.

Ridger



Row width / weight:

43 – 66 cm / 18 kg

The ridger is used in vegetable and potato cultivation. The dams produced reduce the risk of rot and stimulate plant growth.

Full turn plough



Weight: 30 kg

The full turn plough is a special design in which the ploughshare can be rotated when changing lanes. This ensures that the soil is always ploughed in the same direction.



MAKE AN APPOINTMENT. NOW!

We think you should be able to evaluate your new agria before you buy it.

Test the machine on your area and see the performance and quality for yourself. Arrange **your desired appointment** for a **personal demonstration**.

Potato digging plough



Working width / weight:

38 cm / 11 kg

The potato digging plough lifts the potatoes with the surrounding soil. The sieve separates the soil from the potatoes and places the potatoes next to the plough on the surface.

Spring tine cultivator



Working width / weight:

30 – 70 cm / 18 kg

The spring tine cultivator is often used in row crops. It breaks up the topsoil, removes weeds and improves the supply of water and nutrients.

TWO-WHEEL TRACTOR agria 3400

Attachments Green space maintenance and Grounds care

Rotary mulcher



Working width / weight:
80 cm / 98 kg

Rotary mulchers are very suitable for light to medium vegetation. The cuttings are mulched, that means they are cut, shredded and evenly laid down.

NOT ALL MOWERS ARE ALIKE

Mowing is a science apart and you should equip your **agria 3400** with the appropriate attachment depending on your task.

Our mowers and mulchers leave nothing to be desired, whether for visible areas in parks, bushes along roads or for the production of animal feed.

Double knife cutter bar



Working width / weight:
125 cm / 29 kg; 140 cm / 31 kg
160 cm / 35 kg; 180 cm / 40 kg
210 cm / 47 kg

The double knife cutter bar has very low vibration and is therefore gentle on the body. The upper and lower blades move in opposite directions and produce a smooth running.

Portal mowing attachment



Working width / weight:
125 cm / 78 kg; 140 cm / 84 kg
160 cm / 87 kg; 205 cm / 94 kg

The portal mowing attachment is characterised by comfortable operation and low vibrations. With high working widths you can achieve a high area performance.

Belt rake



Working width / weight:
120 cm / 85 kg; 160 cm / 180 kg

After the grass has been cut, it can be turned and swathed with a belt rake. The belt rake can also be used to remove leaves from large areas.

Only for KL-versions

CONSULTING

Individual and sound advice is provided by **agria's dealer network**.



Find a competent dealer near you at **www.agria.de** – quickly and easily.

Weed brush WK 70



Working width / weight:
70 cm Mixed brush / 78 kg
70 cm Flat steel brush / 78 kg

The weed brush WK 70 with its large brush plate removes weeds quickly and effectively. Thanks to the open brush plate, weeds have no chance along edges.


Weed brush B 100



Working width / weight:
100 cm Mixed brush / 186 kg
100 cm Flat steel brush / 186 kg

The weed brush B 100 has two counter-rotating interlocking brush plates and is therefore ideally suited for large-area weed removal.

Surface conditioner



Working width / weight:
90 cm / 135 kg; 100 cm / 142 kg

The surface conditioner removes weeds from water-bounded surfaces such as paths in parks, hiking trails and lanes in cemeteries as well as sports and playing grounds.



agria 3400
with Portal mowing attachment

TWO-WHEEL TRACTOR

agria 3400

Attachments Grounds care

Snowplough



Blade width / weight:
125 cm / 48 kg
 The snowplough is used to remove snow from paths and surfaces that can no longer be swept with a sweeper.

Snow blower



Working width / weight:
85 cm / 110 kg
 With a snow blower even higher snow can be removed quickly. The rotatable chimney ejection allows the precise distribution of the cleared snow.

Spreader



Capacity / weight:
75 Liter / 67 kg
 Spreading salt, sand or chippings is an important addition to snow clearing. The centrifugal spreader distributes the grits very evenly.

Sweeper



Working width / weight:
120 cm / 77 kg
 Sweeping with rotating brush rollers enables large areas to be cleaned quickly and thoroughly of dirt, leaves and snow.

Combined sweeper



Working width / weight:
100 cm rough / 57 kg
100 cm fine / 57 kg
 Combined sweepers have their special feature in the combinability with additional attachments such as a gully brush or a refuse collector bin.

Two-wheel trailer



Dimensions / maximum permissible total weight:
180 x 100 x 30 cm / 650 kg
 Attached to a two-wheel tractor, the trailer can be used to transport materials. To shorten the travel time, a base unit with fast-speed gear is recommended.

Functional options for your agria:

We want you to be able to work ideally with our machines, that's why our base units and attachments are expandable with many useful options, such as wear inserts, additional weights, skids, replacement brushes and much more.

Let us advise you to find the perfect combination for your requirements.

Always the right tyres at hand:



5.00-10
Traction tyres



5.00-12
Traction tyres



23 x 8.50 -12
Traction tyres



21 x 11.00 - 8
Terra tyres



10" Vario
Steel cage wheels

