



Firewalls and Router – IRF1000/3000 series

Maximum security for industrial networks

Simple and intuitive to use, the firewall carries out demanding security tasks and is ideal as remote maintenance centre, router or as IIoT gateway / edge device in a control cabinet.



Industrial Firewalls and Router -
IRF1000 series - IRF3000 series

IRF1000 and IRF3000 series

- > IRF1000 series: Router and firewall for entry-level application with a machine network up to 100Mbit/s
- > IRF3000 series: High-end router and firewall with up to eight subnets and up to 1000Mbit/s
- > Full control over small and large network topologies
- > The operator can easily initiate remote maintenance using a key switch
- > The entire firewall configuration can be stored on a memory card

Industrial Internet of Things – Industry 4.0

- > Integration of common IoT protocols (OPC UA, ModbusRTU and ModbusTCP)
- > Data Push for predictive maintenance, machine learning and other big data applications
- > Connection to any third party cloud via MQTT

Big-LinX® IIoT service- & maintenance-platform

- > Worldwide access to machines and plants via smartcard secured VPN
- > Administration and management of all installed systems
- > Simple data push with Big-LinX

The content of this datasheet was created with utmost care. However, we shall not be held liable for the accuracy, completeness and topicality of any data and figures contained in this publication. The contents are subject to modifications and illustrations may vary. All product names are trademarks and registered trademarks, and as such are the property of the respective company owning trademark rights, in each case.

Technical data



Industrial IT

	IRF14x1	IRF34x1	IRF38x1
CPU	ARM 32-bit 567Mhz	ARM 64-bit 4 x 1,6Ghz	
RAM	512 MB	4 GB	
Flash	4 GB	8 GB	
Network	4 x 100 Mbit/s	4 x 1000 Mbit/s	8 x 1000 Mbit/s
Max. physic. subnets	2	4	8
WWAN	EU or EMEA + US	EU or EMEA + US 5G: Europe	
VPN	Big-LinX, OpenVPN, IPSec		
Firewall operating modes	IP-router (two subnets); transparent bridge	IP-router (two subnets); IP-router extended (up to eight subnets); transparent bridge	
Interfaces	1 x RS485 Half Duplex (ModbusRTU) 1 x SCM card slot 1 x SIM card slot for WWAN with WWAN Modul: 1 x SMA for external WWAN antenna	1 x USB 1 x RS485 Half Duplex (ModbusRTU) 1 x SCM card slot 1 x SIM card slot for WWAN 1 x microSD UHS-II card slot for memory expansion with WWAN Modul: 2 x SMA for external WWAN antenna	1 x USB 1 x RS485 Half Duplex (ModbusRTU) 1 x SCM card slot 1 x SIM card slot for WWAN 1 x microSD UHS-II card slot for memory expansion with WWAN Modul: 2 x SMA for external WWAN antenna 1 x SMA for external GPS antenna
Digital In	1 x	2 x	5 x
Digital Out	-	1 x	4 x
DNV GL	✗	Coming 2023	✗
Operating temperature	30 °C to +70 °C	-20 °C to +70 °C	
Protection class	IP30	IP20	
Dimensions (W x H x D)	94.8 x 134.5 x 29.9 mm	115.0 x 150.0 x 35.0 mm	115.0 x 150.0 x 57.0 mm

ads-tec Industrial IT GmbH
Heinrich-Hertz-Straße 1
72622 Nürtingen/Germany
Phone +49 70222522-200
Fax +49 70222522-402
sales@ads-tec.de
www.ads-tec-iit.com/de

