

Chiller – BR 20 Y

Technical data (219228)

Min leaving water/glycol temperature	°C	-10
Max entering water temperature	°C	15
STD ambient air temperature	°C	35

Hydraulic pump	n°	1
Water flow	m³/h	from 1.8 to 4.8
Tot. Static pressure	kPa	from 290 to 200
Max pressure	Bar	6
Storage tank	litres	100
Water connections	mm	50 (2")

Operation		STANDARD
El. Connections	cable	4 x 6 mm²
Max abs. Power	kW	8,4
Max abs. current MRA	A	17
Starting current	A	49
El. Supply	V/Ph/Hz	400/3/50+PE

Sound pressure level @5m	db (A)	51*
Transport weight	kg	380
Operation weight	kg	490
Transport Length	mm	2.150
Transport Width	mm	1.000
Transport Height	mm	1.650

Optional

Connection cable 4 x 4 mm²

Flexible hoses complete with quick connect coupling 2" / 50 mm



* Free field sound pressure level taken at 1 m from the unit and 1,5 m from its base, compressors side and full operating unit without hydraulic kit. The sound pressure level may change according to the various installation and has a +/- 3 dB(A) tolerance according to ISO 3744.

Emissione: 03/2024

BRENTA RENT S.r.l. Sede Legale: Via Alsazia, 3 sc. A/10 - 35127 PADOVA Cap. sociale € 12.000,00

Sede Operativa ed amministrativa: **Via dell'Industria, 17 - 35020 ARZERGRANDE (PD)**

e.mail: brenta@brentarent.it www.brentarent.it PEC: brentarent@pec.it

tel. +39 049 5800034

P.I./C.F.: 03667010288 N° REA: PD 327292

AZIENDA CON
SISTEMA DI GESTIONE QUALITA'
CERTIFICATO DA DNV
ISO 9001