





iXpro[®] Your Gateway solution

Give your IoT the right direction

helloiot@ithinx.io • www.ithinx.io/






Your innovative IoT technology partner

About ithinx


About iThinX




PCB and Antenna development



- Development of antennas: Compact, integrated, multiband, tunable apertures
- PCB design for wired and wireless communication systems
- Approval and market launch according to CE, RED, FCC, ISED, RTA, UL, CCC, EMC, Safety




System testing



- ISTQB certified test engineers
- Fully automated test environment using Robot Framework
- Test executions and reports highly integrated in Jira and Polarion workflows


EMC and RF Performance Measurements



- Fully Anechoic Room (FAR)
- Vector network and spectrum analysers
- Radio communication & protocol testers
- 3D EM simulation solutions (antenna design, signal integrity, thermal)



Software development



- Low level driver and BSP development for Linux and RTOS systems
- IoT frameworks and high level customer application design
- Agile way of working with fully integrated CI/CD process

About **i**thinx



Smart Lighting Outdoor

Development of a multi-radio IoT hardware to control outdoor lighting systems in compliance with all relevant regulations for outdoor applications.



Smart Audio System

Development of IoT hardware and software to control and operate a digital audio system in compliance with all relevant regulations for use by children.



Product references

Smart Lock


Development of all radio and wired connectivity solutions of a scalable locking system.



Smart Climate

Development of smart products for intelligent air conditioning and heating/cooling controls.





Your gateway to the market

iXpro[®] Gateway

iXpro - the core of your IoT product

HF expertise and world wide support

- Developed in collaboration between ithinx and NXP

Compact design

- Smallest Design for Wireless incl. antenna and uP integration 120mmx110mmx21,5mm

Multiprotocol

- Supporting Wifi6*, Bluetooth*, Thread, Zigbee and Cellular (LTE Cat1 to GNSS)

Built for Matter

- Extendable with our Matter Bridge application or usable as Matter Controller

Easily integrated


- USB, CAN, RS485, Ethernet, GPIO, UART, I2C, SPI, ADC

Advanced health management

- 6-axis accelerometer, temperature sensor and voltage measurements

Quick to market

- Low Cost and integrated antenna (patented)




*precertified module

iXpro - the ingredients


Key facts	
Processor	i.MX9331 - 1x A55 @ 1.7GHz (opt. i.MX9352 - 2x A55 @ 1.7GHz + NPU)
DDR	512MB LPDDR4x (opt. up to 2GB)
eMMC	8GB (opt. up to 256GB)
Power supply	9..36V DC
Buffered RTC (optional)	72h+, high precision ± 1 ppm (@ 25°)
Additional feature (optional)	6-axis accelerometer, NTC
Operating temp. range	-25..+85°C (opt. -40..+85°C)
Dimensions	110x120mm ²
SIM	eSIM (MFF2) (opt. MicroSIM card holder)

Interfaces			
Wireless		Wired	
Wi-Fi	Wi-Fi 5 / 6	Ethernet	1x ETH (10/100 BASE-T)
LP RF	Bluetooth 5.3/LE, 802.15.4 (ZigBee or Thread)	USB	2x USB 2.0 (480 Mbit/s, 1x USB-C, 1x USB-A)
Cellular	CAT1bis (opt. incl GNSS)	CAN	1x CAN 2.0b
		RS485	1x
		HMI	4x LED
		5V out	1x
		LVDS	1x
		30-pin connector	1x including USB, UART, GPIO, ADC, I2C, SPI (for piggyback extension)

iXpro - Block diagram full variant



iXpro - new additional extension options




Further connectivity options available

- DALI
- LoRa
- EnOcean
- Your own module of choice



...






iXpro[®] SMARC

Small and handy

iXpro SMARC – About

- SMARC? -> Short for 'Smart Mobility ARChitecture' is a popular global standard specification for Computer-on-Modules (CoM) and is often used as a design standard for modular embedded computing.
- The basis is our iXpro gateway architecture
- Standardised form factor of 82x50mm²
- Available soon



iXpro SMARC – Feature overview

Category	Facts	Optional
CPU	Dual Core ARM Cortex A55@1.7GHz, ARM Ethos U65 NPU (up to 0.5 TOPS) ARM Cortex M33 @ 250MHz, EdgeLock Secure Enclave subsystem	Single Core ARM Cortex A55,
Memory / Storage	LPDDR4x up to 3700MT/s, x16 data bus, up to 2GB (default), eMMC v5.1 8GB, (up to 256GB possible)	EEPROM (on I ² C bus)
Display support	LVDS up to 1366x768p60 or 1280x800p60 MIPI DSI up to 1920x1200, 60Hz	
Camera support	MIPI-CSI, 2 lanes	
Connectivity	2x 10/100/BASE-T Ethernet Dual-Band Wi-Fi 6, 1x1, Dual Mode Bluetooth 5.3, External antenna (u.FL connector) and on-board (TBC) antenna options	
Interfaces	1x USB2.0 OTG + 1x USB2.0 host 4x UART (2x with HW handshake) 1x SD card interface 2x SPI 4x I2C, 400kHz 2x CAN FD MAC 14x GPIO <div style="display: inline-block; vertical-align: middle; margin-left: 20px;"> } SMARC 2.1.1 compliant, 314pin MXM edge connector </div>	1x USB2.0 OTG + 4x USB2.0 host (via USB hub)
Temperature Range	-40...+85°C	
Power Supply	5V DC	

“Give your
IoT solution the
right direction“

